


# Observed ground motion basin amplifications and modelling for future events





Brendon Bradley, University of Canterbury, New Zealand  
Director, QuakeCoRE: The NZ Centre for Earthquake Resilience

---


What have we directly observed at Wellington ground motion stations in the 2016 Kaikōura, and other moderate magnitude, earthquakes?

# Observations – Kaikōura 2016




(Bradley et al, 2018)


# Observations – Kaikōura 2016



(a)



(b)




(c)


Large vertical  $S_a(T \sim 1.5)$  amplitudes due to converted Rayleigh waves



# Observations – multiple $M > 6$ events



# Obs. Spectral ratios – Multiple events




- Key trends:
  - For  $T \sim 1.5s$ , amplifications,  $AF \sim 3-7$
  - For  $T > 5s$ ,  $AF \sim 1$
- The “Site C/D boundary discussion” in Wellington (based on geotechnical definitions) is detached from reality (the amplifications we actually observe)

---


What are the salient phenomena that give rise to these observations at 'basin' sites?

# Reflection, refraction and impedance

## Reflection and refraction of transmitted wave




## Effect of impedance (on amplitude) and multiple layers







# Critical refraction / total internal reflection




# Critical refraction / total internal reflection



# Impedance vs. basin-edge illustration



(Graves, 1993)



---


## Historical examples of basin-edge effects

# Loma Prieta (1989) – Marina District

## Marina District Stations

(Graves, 1993)


Location and instruments






# Loma Prieta (1989) – Marina District


Marina District Stations



Relative Peak Velocity





Duration (sec)





Map indicating "Damage belt"

The map shows the Kobe area with various districts labeled: Nishinomiya, Takarazuka, Itami, Higashinada-w., Ashiya, Nada-w., Kobe Univ., JMA Kobe, Chuo-w., Ashiya F., Koyo F., Amagasaki, Hyogo-w., Suwayama F., Nagata-w., Suma-w., Suma F., Egawa F., Tarumi-w., Kobe Port Office, Port Island, and Amagasaki. A dark shaded area represents the "Damage belt" along the coast. A scale bar indicates 5km. A legend shows a dark oval representing "JMA Intensity VII".

The diagram illustrates a numerical model for seismic response analysis. It shows a cross-section of the ground with a grid mesh. Key features include the Suwayama F. (Suwayama Fault), JR Sannomiya, Hanshin Expressway, and Port Island. The model is bounded by transmitting boundaries on the left and right, and a viscous boundary at the bottom. The total width of the model is 3960m. The seismic wave velocities are indicated:  $V_p=550\text{m/s}$ ,  $V_s=450\text{m/s}$ ,  $V_p=650\text{m/s}$ ,  $V_s=1000\text{m/s}$ , and  $V_s=2500\text{m/s}$ .





# Northridge (1994) – Santa Monica








# Canterbury (2010-2011) - Heathcote Valley



$t=3.3$  s



(b)



---

How can we quantify these basin effects?



# Quantification of 'basin' effects

---

- Empirical representation
  - Direct modification of code-based spectral shapes
  - Modification of empirical ground motion models (that underpin code spectra)


Easier to develop; extrapolation problems (spatially within a region and for different regions; effects of source location relative to basin; consideration of ground motion amplitude)

- Physics-based representation
  - Simulations that explicitly model basin effects

Harder to develop; more generalizable (physics provides framework for extrapolation)

# Empirical representation of basin effects



---



---


# Adjustment factors for code-oriented utilisation

# Code-oriented empirical adjustment





- 19 historical events with  $M > 5$
- Compared with site class D spectra

# Code-oriented empirical adjustment





# Code-oriented empirical adjustment




Empirical adjustment that is a function of:

- Distance from basin edge (Waterfront is  $\sim 0.5$ - $0.7$  km)
- Vibration period (largest at  $T = 1.5$  s)

---


What do empirical ground motion models tell  
us?

# Comparison with empirical ground motion models



# Comparison with empirical ground motion models

## Empirical perspective on nonlinear effects



- In Kaikoura event  $SA(1s) \sim 0.4g$
- Design  $SA(1s)$  for site class D = 0.75g.
- Nonlinearity effect decreases with increasing amplitude

---

# The use of physics-based simulations





# Physics-based representation

---


- Limitations of empirical approach
  - What to do for other regions of NZ (many of which are located in sedimentary basins)?
  - Interaction of the basin 3D geometry with the source location (back-azimuth)
  - Effects that are not seen in the observational data, specifically in Wellington, associated with larger magnitude events (longer duration of shaking/resonance, nonlinear surficial soil)

# Explicit modelling of sedimentary basins

## Wellington and NZ-wide




# Example simulation of historical event



Video here: <https://www.youtube.com/watch?v=kDJn9bMEQo8>




# Example simulation of historical event



Video here: <https://www.youtube.com/watch?v=kDJn9bMEQo8>


# Example simulation of Hikurangi rupture



Video here: <https://www.youtube.com/watch?v=55RhqF7xc78>




# Example simulation of Hikurangi rupture



Video here: <https://www.youtube.com/watch?v=55RhqF7xc78>


# Example simulation of Hikurangi rupture



Video here: <https://www.youtube.com/watch?v=55RhqF7xc78>




# Example simulation of Hikurangi rupture




Video here: <https://www.youtube.com/watch?v=55RhqF7xc78>

# Using simulations to constrain empirical ground motion model 'extrapolation'

Interface: Global, M9, Vs400, PGA



Interface: Global, M9, Vs400, T=3sec



# Conclusions (1/2)

---

The 2016 Kaikōura earthquake highlighted the significant amplifications of ground motion over short distances due to near-surface soils and 'basin' effects

- 'Basin' effects comprise both amplification due to impedance (from stiff to soft soils), as well as 'edge' effects associated with refraction and critical reflection at the basin edge
- These effects have been seen systematically in major historical earthquakes internationally, as well as in New Zealand, and are supported by simulation evidence
- They are a geometric problem and therefore are repeatable (with some level of 'variation' due to complexities in the phenomena)
- They also will be present in all sedimentary basins in NZ – the specific impact will depend on:
  - (i) the stiffness of the sedimentary soils [i.e. the impedance ratio];
  - (ii) the geometry (including depth) of the basin.

Which will influence the degree of basin amplification, and the vibration periods where it is most pronounced.

## Conclusions (2/2)

---

### Accounting for basin effects in seismic hazard and design, going forward


- Adjustment factors for design codes/standards to reflect first-order features of differences between observations and present code/standards
- Use of site-specific studies that can model these effects explicitly
- Increasing role of simulations to supplement/replace empirical methods of ground motion prediction to advance scientific understanding
- Science feeds into revised seismic hazard analyses nationwide that can underpin updates to codes/standards

# References

---

- Bradley, B. A., Wotherspoon, L. M., Kaiser, A. E., Cox, B. R. & Jeong, S. Influence of Site Effects on Observed Ground Motions in the Wellington Region from the Mw 7.8 Kaikōura, New Zealand, Earthquake. *Bulletin of the Seismological Society of America* **108**, 1722–1735 (2018).
- Graves, R. W. Modeling three-dimensional site response effects in the Marina District Basin, San Francisco, California. *Bulletin of the Seismological Society of America* **83**, 1042–1063 (1993).
- Kawase, H. The Cause of the Damage Belt in Kobe: ‘The Basin-Edge Effect,’ Constructive Interference of the Direct S-Wave with the Basin-Induced Diffracted/Rayleigh Waves. *Seismological Research Letters* **67**, 25–34 (1996).
- Graves, R. W., Pitarka, A. & Somerville, P. G. Ground-motion amplification in the Santa Monica area: Effects of shallow basin-edge structure. *Bulletin of the Seismological Society of America* **88**, 1224–1242 (1998).
- Jeong, S. & Bradley, B. A. Amplification of Strong Ground Motions at Heathcote Valley during the 2010–2011 Canterbury Earthquakes: The Role of 2D Nonlinear Site Response. *Bulletin of the Seismological Society of America* **107**, 2117–2130 (2017).
- Chiou, B. S. J. & Youngs, R. R. An NGA Model for the average horizontal component of peak ground motion and response spectra. *Earthquake Spectra* **24**, 173–215 (2008).
- Kaiser, A. E. *et al.* Updated 3D basin model and NZS1170.5 subsoil class and site period maps for the Wellington CBD: Project 2017-GNS-03-NHRP. (2019).
- Thomson, E. M., Bradley, B. A. & Lee, R. L. Methodology and computational implementation of a New Zealand Velocity Model (NZVM2.0) for broadband ground motion simulation. *New Zealand Journal of Geology and Geophysics* **63**, 110–127 (2020).
- Kuehn, N. M *et al.* *Partially non-ergodic ground-motion model for subduction regions using NGA-subduction database*. PEER Report 2020 (forthcoming)





Thank you for your attention

<https://sites.google.com/site/brendonabradley/>



QuakeCoRE  
NZ Centre for Earthquake Resilience



an NSF + USGS center

